

Specifications

DEMAND MODEL NAME	MINERAL CU. FT.	LOW SALT GRAINS/LBS.	CAPACITY MED. SALT GRAINS/LBS.	HIGH SALT GRAINS/LBS.	FLOW RATE @ 15 PSI	PEAK FLOW RATE @ 25 PSI	BACK WASH RATE GPM	MINERAL TANK (INCHES)	BRINE TANK'	
									TANK SIZE (INCHES)	SALT STORAGE (POUNDS)
H200L-60	2	38,000/12	56,000/20	64,000/30	34	44	4.2	1354	18x40	330
H200L-90	3	57,000/18	84,000/30	96,000/45	34	44	4.2	1465	18x40	300
H200L-120	4	76,000/24	112,000/40	128,000/60	41	53	5.3	1665	24x41	640
H200L-150	5	95,000/30	140,000/50	160,000/75	46	59	7.5	1865	24x50	750
H200L-150-21	5	95,000/30	140,000/50	160,000/75	54	68	9.0	2162	24x50	750
H200L-180	6	114,000/36	168,000/60	192,000/90	44	56	7.5	1865	24x50	750
H200L-180-21	6	114,000/36	168,000/60	192,000/90	53	67	9.0	2162	24x50	750
H200L-210	7	133,000/42	196,000/70	224,000/105	51	66	9.0	2162	24x50	710
H200L-240	8	152,000/48	224,000/80	256,000/120	58	74	12.0	2460	24x50	680
H200L-270	9	171,000/54	252,000/90	288,000/135	55	72	12.0	2471	30x50	1110
H200L-300	10	190,000/60	280,000/100	320,000/150	54	70	12.0	2471	30x50	1110