

MODEL NAME	RESIN CU. FT.	CAPACITY			SERVICE FLOW RATE CONT. 15 PSI	FLOW RATE PEAK 25 PSI	BACKWASH RATE GPM	MINERAL TANKS (INCHES)	BRINE TANK SIZE (INCHES)	SALT STORAGE (POUNDS)	SHIPPING WEIGHT (POUNDS)	INLET/OUTLET HEIGHT (INCHES)
		LOW SALT GRAINS/LBS	MED. SALT GRAINS/LBS	HIGH SALT GRAINS/LBS								
NF-60	2.0	38,000/12	56,000/20	64,000/30	23.0	32.0	3.5	13 x 54	18 x 40	375	404	57.5
NF-90	3.0	57,000/18	84,000/30	96,000/45	22.0	30.0	4.0	14 x 65	18 x 40	375	539	68.5
NF-120	4.0	76,000/24	112,000/40	128,000/60	25.0	34.0	5.0	16 x 65	24 x 41	525	677	68.5
NF-150-18	5.0	95,000/30	140,000/50	160,000/75	27.0	37.0	7.0	18 x 65	24 x 50	510	832	70.5
NF-150-21	5.0	95,000/30	140,000/50	160,000/75	31.0	41.0	9.0	21 x 62	24 x 50	510	946	70.5
NF-180-18	6.0	114,000/36	168,000/60	192,000/90	26.0	35.0	7.0	18 x 65	24 x 50	510	938	70.5
NF-180-21	6.0	114,000/36	168,000/60	192,000/90	30.0	40.0	9.0	21 x 62	24 x 50	510	1052	70.5
NF-210	7.0	133,000/42	196,000/70	224,000/105	29.0	39.0	9.0	21 x 62	24 x 50	510	1158	70.5
NF-240	8.0	152,000/48	224,000/80	256,000/120	32.0	42.0	12.0	24 x 72	24 x 50	340	1332	78.0
NF-270	9.0	171,000/54	252,000/90	288,000/135	31.0	41.0	12.0	24 x 72	24 x 50	340	1438	78.0
NF-300	10.0	190,000/60	280,000/100	320,000/150	30.0	40.0	12.0	24 x 72	24 x 50	340	1544	78.0

- Cubic feet of mineral and capacities as seen above are per mineral tank.
- Service flow ratings are with the 1.5" meter.
- Limit of 2 ppm of ferrous iron. Add 3 grains of hardness per ppm of iron when sizing.
- See owners manual for specific operating details
- These conditioners will not purify or make your water safe to drink.
- Product improvements and design changes subject to change without notice.
- Water Pressure 30 - 100 psi.
- Water temperature is not to exceed 110°F and cannot be subject to freezing conditions.
- Inlet/outlet heights are approximate only.