

## PROMATE 6 IRON CURTAIN 2.0 SPECIFICATIONS

<b>Models</b>	<b>Filter &amp; Aeration Tank Size</b>	<b>Media Cu. Ft</b>	<b>(1) Inlet/Outlet</b>	<b>Max. Service Flow GPM</b>	<b>(2) Backwash Rate GPM</b>	<b>Floor Space (WxHxD)</b>
<b>IC-10</b> PM6.0-IC2.0	10"x54"	1.5	1"	5.0	5.0	26"x68"x16"
<b>IC-10A</b> PM6.0-IC10A-2.0	10"x54"	1.5	1"	5.0	5.0	26"x68"x16"
<b>IC-10+</b> PM6.0-IC10A-2.0	10"x54"	1.5	1"	5.0	5.0	26"x68"x16"
<b>IC-12</b> PM6.0-IC12A-2.0	12"x52"	2.0	1"	7.0	8.0	30"x66"x18"
<b>IC-12A</b> PM6.0-IC12A-2.0	12"x52"	2.0	1"	7.0	8.0	30"x66"x18"
<b>IC-12+</b> PM6.0-IC12A-2.0	12"x52"	2.0	1"	7.0	8.0	30"x66"x18"
<b>IC-13</b> PM6.0-IC13A-2.0	13"x54"	3.0	1"	8.0	10.0	32"x68"x20"
<b>IC-13A</b> PM6.0-IC13A-2.0	13"x54"	3.0	1"	8.0	10.0	32"x68"x20"
<b>IC-13+</b> PM6.0-IC13A-2.0	13"x54"	3.0	1"	8.0	10.0	32"x68"x20"

(1) Aeration Head and Check Valve have 1" Inlet/Outlet.

(2) Water temps above 60° F will require a higher backwash rate. Consult factory.