



HVN Specifications

Model Number	Resin Cu. Ft.	Exchange Capacity			Service Flow Rates (GPM)				Inlet/Outlet Pipe Size	Mineral Tank Size	Backwash Rates	
		Low Salt Grains @ Lbs.	Med. Salt Grains @ Lbs.	High Salt Grains @ Lbs.	@ 10 GPM Per Sq.	@ 13 GPM Per Sq.	@ 15 PSI	@ 25 PSI			Cld Wtr GPM	Wrm Wtr GPM
HVN-15-2	15	300@90	390@150	450@225	50	65	78	109	2	30x60	20	25
HVN-15-2.5	15	300@90	390@150	450@225	50	65	114	161	2.5	30x60	20	25
HVN-15-3	15	300@90	390@150	450@225	50	65	133	180	3	30x60	20	25
HVN-20-2	20	400@120	520@200	600@300	70	90	104	118	2	36x60	30	35
HVN-20-2.5	20	400@120	520@200	600@300	70	90	133	180	2.5	36x60	30	35
HVN-20-3	20	400@120	520@200	600@300	70	90	166	237	3	36x60	30	35
HVN-25-2	25	500@150	650@250	750@375	70	90	85	110	2	36x72	30	35
HVN-25-2.5	25	500@150	650@250	750@375	70	90	133	180	2.5	36x72	30	35
HVN-25-3	25	500@150	650@250	750@375	70	90	152	218	3	36x72	30	35
HVN-30-2	30	600@180	780@300	900@450	100	125	99	126	2	42x60	40	50
HVN-30-2.5	30	600@180	780@300	900@450	100	125	142	207	2.5	42x60	40	50
HVN-30-3	30	600@180	780@300	900@450	100	125	178	265	3	42x60	40	50
HVN-40-2	40	800@240	1040@400	1200@600	125	165	115	130	2	48x60	50	60
HVN-40-2.5	40	800@240	1040@400	1200@600	125	165	150	175	2.5	48x60	50	60
HVN-40-3	40	800@240	1040@400	1200@600	125	165	200	285	3	48x60	50	60
HVN-50-2.5	50	1000@300	1300@500	1500@750	160	210	155	180	2.5	54x60	65	80
HVN-50-3	50	1000@300	1300@500	1500@750	160	210	210	290	3	54x60	65	80
HVN-60-2.5	60	1200@360	1560@600	1800@900	200	255	155	180	2.5	60x60	80	100
HVN-60-3	60	1200@360	1560@600	1800@900	200	255	220	305	3	60x60	80	100
HVN-60-4	60	1200@360	1560@600	1800@900	200	255	420	615	4	60x60	80	100
HVN-80-3	80	1600@480	2080@800	2400@1200	240	310	230	320	3	66x72	95	120
HVN-80-4	80	1600@480	2080@800	2400@1200	240	310	455	655	4	66x72	95	120
HVN-100-3	100	2000@600	2600@800	3000@1500	280	370	240	335	3	72x72	115	140
HVN-100-4	100	2000@600	2600@800	3000@1500	280	370	475	680	4	72x72	115	140

Updated 2/02-LBRY